



B2	BL2	S2	M2	L2	XLm2	XL2
Dimensions (HxWxD) : 337mm x 223mm x 339mm	Dimensions (HxWxD) : 400mm x 265mm x 402mm	Dimensions (HxWxD) : 950mm x 230mm x 401mm	Dimensions (HxWxD) : 1108mm x 272mm x 472mm	Dimensions (HxWxD) : 1240mm x 336mm x 581mm	Dimensions (HxWxD) : 1710mm x 272mm x 472mm	Dimensions (HxWxD) : 1918mm x 336mm x 581mm
Weight : 10 kg	Weight : 15 kg	Weight : 31 kg	Weight : 45 kg	Weight : 75 kg	Weight : 95 kg	Weight : 115 kg
Shipping weight : 12 kg	Shipping weight : 18 kg	Shipping weight : 34 kg	Shipping weight : 49 kg	Shipping weight : 82 kg	Shipping weight : 125 kg	Shipping weight : 157 kg
Sensitivity : 89.5 dB @ 2.83V 1m	Sensitivity : 90.5 dB @ 2.83V 1m	Sensitivity : 91 dB @ 2.83V 1m	Sensitivity : 91.5 dB @ 2.83V 1m	Sensitivity : 92 dB @ 2.83V 1m	Sensitivity : 92 dB @ 2.83V 1m	Sensitivity : 92 dB @ 2.83V 1m
Suggested amp power : 5-150 W;	Suggested amp power : 10-200 W;	Suggested amp power : 10-250 W;	Suggested amp power : 10-300 W;	Suggested amp power : 20-500 W;	Suggested amp power : 20-700 W;	Suggested amp power : 20-900 W;
Impedance : nominal 4, 0 ohms	Impedance : nominal 8, 0 ohms	Impedance : nominal 8, 0 ohms				
Crossover frequency : 4000 Hz	Crossover frequency : 4000 Hz	Crossover frequency : 400 Hz; 4000 Hz	Crossover frequency : 400 Hz; 4000 Hz	Crossover frequency : 400 Hz; 4000 Hz	Crossover frequency : 400 Hz; 4000 Hz	Crossover frequency : 400 Hz; 4000 Hz
Frequency response (in-room environment) : 42-25000 Hz	Frequency response (in-room environment) : 39-25000 Hz	Frequency response (in-room environment) : 35-25000 Hz	Frequency response (in-room environment) : 30-25000 Hz	Frequency response (in-room environment) : 24-25000 Hz	Frequency response (in-room environment) : 28-25000 Hz	Frequency response (in-room environment) : 24-25000 Hz



MEET THE ALL-NEW FIGARO!
AN EVOLUTION OF OUR MOST SUCCESSFUL SPEAKER SERIES.

AVAILABLE IN

AZURE BLUE

CAFE BROWN

FERN GREEN

MAROON RED

PEARL WHITE

中國（包括香港，澳門地區）總代理



君庭影音工程有限公司
Granding Audio Video Engineering Limited